

Beckhoff — CP Panel PC Systems

CP2915-1013-0000 **In-Stock, Ships Today**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer

**Secure Online**
Checkout**Free Ground**
Shipping**One Year**
Warranty

The **CP2915-1013-0000** is a panel-mount industrial PC manufactured by Beckhoff and supplied within the CP Panel PC Systems series. Installed on machine fronts or control cabinets, the unit combines computing power with an integrated display so that PLC programs and visualization software can run locally while operators interact directly through the front glass. By replacing separate box PCs and monitors, it streamlines human-machine interface tasks in packaging lines, processing equipment, and material-handling cells.

The built-in display measures **15 inches diagonally** and presents process graphics at a native resolution of **1024 × 768 pixels**. Its **4:3 image format** accommodates legacy SCADA layouts and other applications designed for a conventional aspect ratio. Images reach the panel through the DVI Extended interface. The sealed aluminum front has an **IP65 rating**, allowing washdown on the machine side while ventilation occurs at the protected rear. The electronics operate on **24 VDC**, so the panel can connect directly to common auxiliary power rails without additional converters.

Internal wiring terminates on spring-loaded clamps that accept conductors up to 1.5 mm², and the power plug remains securely latched during operation. The connector supports a minimum supply voltage of 22 V and a current limit of 16 A. The rear housing has an **IP20 rating**, which protects against accidental contact with internal electrical components after the unit is installed inside an enclosure. Operator input is captured by a **projected capacitive touch interface with Multi-Finger Touch (PCT)** recognition, allowing multiple simultaneous touch inputs. The DVI link supports cable runs of up to **50 m** without signal repeaters. Two downstream USB ports and one upstream

Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.

USB port are routed through an RJ45-style connection for peripheral access. The system weighs **3.7 kg**, making it suitable for installation on swing arms or in flush-mounted panels.

Specifications

Aspect Ratio:	4:3	Display Interface:	DVI Extended	Display Resolution:	1024 x 768
Display Size:	15-inch	Front Protection Rating:	IP65	Housing:	Aluminum
Interface:	DVI, USB	Max Dvi Distance:	50 m	Max Wire Cross-section:	1.5 mm²
Minimum Plug Voltage:	22 V	Multitouch:	Yes	Nominal Voltage:	24 VDC
Operating Temperature:	"0 to 55 0C"	Power Connector Rating:	16 A	Product Type:	Control panel
Protection Rating:	IP65 (front), IP20 (back)	Rear Protection Rating:	IP20	Resolution:	1024 x 768
Touch Screen:	Multi-Finger Touch (PCT)	Usb Extended Port:	RJ45	Usb Inputs:	1
Usb Outputs:	2	Weight:	3.7 kg	Last Verified:	10/25/2026 3:49 PM

Contact Us

-  1620 Old Apex Road, Cary, NC 27513, USA
-  Toll Free: [1-888-551-3082](tel:1-888-551-3082)
-  International: [1-919-443-0207](tel:1-919-443-0207)
-  Fax: [1-919-867-6204](tel:1-919-867-6204)
-  Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.