

Beckhoff - IE Extension Box Series

IE6002-0000



 **Request a Quote**

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **IE6002-0000** is a part of the **IE Extension Box Series** by **Beckhoff**.

Specifications

Data Transfer Channels:	2 (1/1), Tx/D and Rx/D	Data Transfer Rates:	1200)115,200 baud, 9600 baud (8 bits, no parity, 1 stop bit) is preset	Rs232 Connection:	M12, screw type
Nominal Voltage:	24 V DC (-15%/+20%)	Bit Transfer:	RS232 (EIA-232)	Bit Distortion:	< 3%
Cable Length:	max. 15 m	Data Buffer:	128 bytes receive buffer, 16 bytes transmit buffer	Power Supply Connection:	feed: 1 x M8 male socket, 4-pin, a-coded; downstream connection: 1 x M8 female socket, 4-pin, a-coded
Current Consumption From Us (without Sensor Current):	40 mA	Bit Width In The Process Image:	input/output: 3 x 8 bit user data, 1 x 8 bit control/status (up to 5 x 8 bit user data are possible)	Operating/storage Temperature:	0)+55°C/-25) +85°C
Contact Us	conforms to EN 60068-2-6/EN 60068-2-27	Shipping Options	12/27/2024 8:02		
Vibration/shock					
Residual Current					

Contact Us
Vibration/shock
Residual Current
11620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods

