

B & R Automation - 4B1 PanelWare Panels

4B1270.00-K09



 **In-Stock, Ships Fast**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **4B1270.00-K09** is a part of the **4B1 PanelWare Panels Series** by **B & R Automation**.

Specifications

Address/baud Setup:	Hex Switches	Backlight Colors:	Yellow/Green	Can Connector:	9-pin D-Sub (Male)
Can Isolation:	Electrically Isolated	Can Pinout (d-sub):	2=L, 3=GND, 7=H	Compatible Pulley Diameter:	Standard for B section, minimum ~125 mm
Contrast Adjustment:	Via Keys	Display Brightness:	200 cd/cm2	Display Resolution:	4 x 20 Characters
Display Type:	LC	Fieldbus Interface:	CAN	Humidity Condition:	Non-Condensing
Keypad Type:	Membrane	Length:	1270 mm	Material:	Rubber with fabric cords (standard for industrial V-belts)
Nominal Supply Voltage:	24 VDC	Number Of Ribs:	4	Power Connector:	3-pin Terminal Block
Rohs Compliance:	Yes (typical)	Section:	B	Temperature Range:	-30°C to +80°C (typical for industrial belts)
Tensile Strength:	Dependent on manufacturer; typically >1200 N	Type:	V-Belt	Weight:	Varies (~0.13 kg per meter for B-section)

Contact Us

Width: 1620 Old Apex Road, Cary, NC 27513, USA **Last Verified:**

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@wakeindustrial.com

Shipping Options

06/11/2024 5:06 PM



Payment Methods

