

B & R Automation - 4PP Power Panels

4PP280.1043-K01



 Available, Ships in 1-2 weeks

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **4PP280.1043-K01** is a part of the **4PP Power Panels Series** by **B & R Automation**.

Specifications

Brightness:	350 cd/m ²	CompactFlash Slot:	Type I	Contrast Ratio:	600:1
Dimensions (w X H X D):	315 x 238 x 55 mm	Display Diagonal:	10.4 in (264 mm)	Display Resolution:	640 x 480 pixels
Display Size:	10.4 inches	Display Type:	TFT color display	Ethernet Interface Transfer Rate:	10/100 Mbit/s
Flash Memory:	2 GB	Front Protection:	IP65 (NEMA Type 4X)	Function Keys:	12 with LED
Interfaces:	Ethernet, USB, Serial	Mounting Method:	Panel mounting	Nominal Voltage:	24 VDC ±25%
Operating Temperature:	0 degrees C to +55 degrees C	Power Consumption:	25 W (Max)	Power Supply:	24 V DC (18-30 VDC)
Processor:	Intel Atom	Processor Clock:	266 MHz	Processor Type:	Geode SC2200
Protection Class:	IP65 (front), IP20 (rear)	Ram:	512 MB	Resolution:	640 x 480 pixels (VGA)
Serial Interface:	RS232 9-pin D-Sub	Soft Keys:	10 with LED	Touch Screen:	Analog resistive
Touch Technology:	Analog Resistive	Usb Interface:	2x USB 1.1 Type A	Weight:	Approx. 2.7 kg
Last Verified:	06/12/2026 8:02 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

