

B & R Automation - 4PP Power Panels

4PP420.0571-K14



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **4PP420.0571-K14** is a part of the **4PP Power Panels Series** by **B & R Automation**.


Specifications

Bleeder resistance:	0 ?
Cpu Clock Frequency:	500 MHz
Dimensions (w x H x D):	212 x 156 x 76 mm
Display Type:	TFT color display
Memory (ram):	128 MB
Nominal voltage:	18 to 30 VDC
Power Supply:	24 V DC
Resolution:	320 x 240 (QVGA)
Storage:	CompactFlash/SD slot for memory expansion
Touchscreen Technology:	Analog Resistive

Communication Interfaces:	Ethernet, RS232, RS422/485, 2 x USB (Host and Device)
Cpu Type:	Geode LX800
Display Diagonal:	5.7 in
Ethernet Transfer Rate:	10/100 Mbit/s
Mounting:	Panel mounting
Operating Temperature Range:	0 °C to +55 °C
Processor:	Geode LX800
SDRAM:	128 MB
Touchscreen:	Analog resistive
Last Verified:	06/20/2016 8:41 AM

Cooling Method:	Passive via heat sink
Dimensions:	Approx. 156 x 212 x 76 mm
Display Size:	5.7 inch
Front Protection:	IP65
Nominal current:	0.5 A
Power Consumption:	Approx. 7 W
Protection Class:	IP65 (front), IP20 (rear)
SRAM:	512 kB Battery-Backed
Touchscreen Controller:	Elo 12-bit

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

