

B & R Automation - 4PP Power Panel Series

4PP220.1043-K10



 [Request a Quote](#)

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **4PP220.1043-K10** is a part of the **4PP Power Panel Series** by **B & R Automation**.

Specifications

Display:	TFT color	CPU:	AMD Geode LX800, 500 MHz, 32-bit x86 architecture	Cache Memory:	128 kB L1 and 128 kB L2 caches
Cooling System:	Passive cooling with heat sink	Flash Memory:	2 MB for firmware storage	Connectivity:	1 Ethernet port (10/100 Mbps), 1 RS232 serial port, 2 USB ports
Power Input:	24 VDC, typical power consumption of 30 W	Operating Temperature Range:	0 to 50 degrees C	Ingress Protection Rating:	IP65 (front), IP20 (rear)
Vibration Resistance:	2 to 9 Hz at 1.75 mm amplitude, 9 to 200 Hz at 0.5 g	Last Verified:	12/02/2024 1:35 PM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.