

B & R Automation - 4PP Power Panel Series

4PP452.0571-B5



 [Request a Quote](#)

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **4PP452.0571-B5** is a part of the **4PP Power Panel Series** by **B & R Automation**.

Specifications

Processor:	Geode LX800 500 MHz, 32-bit x86	Memory:	128 MB DDR SDRAM	Display Type:	Color TFT
Display Diagonal:	5.7 inch (144 mm)	Display Resolution:	QVGA, 320 x 240 pixels	Touch Screen Type:	Not applicable
Ethernet:	Intel 82551ER, 10/100 Mbit/s	Serial Interface:	RS232, modem- capable, not electrically isolated, 16C550 compatible, 16- byte FIFO, Max. 115 kBaud, 9-pin DSUB	Usb Interface:	2 x USB 1.1, USB 2.0, Type A, Max. 500 mA per connection
Power Supply:	18 - 30 VDC, 0.63 A	Power Consumption:	Typically 15 W	Operating Temperature:	0 to +50 degrees C
Protection:	IP65 / NEMA 250 type 4X (front side)	Dimensions:	302 mm (Width) x 187 mm (Height) x 98 mm (Depth)	Weight:	Approx. 2.9 kg
Last Verified:	12/03/2024 5:49 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

