

B & R Automation - 4PP Power Panel Series

4PP480.1505-75



 [Request a Quote](#)

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **4PP480.1505-75** is a part of the **4PP Power Panel Series** by **B & R Automation**.

Specifications

Boot Loader / Operating System:	Automation Runtime	Processor Type:	Geode LX800 500 MHz, 32-bit x86	L1 Cache:	128 KB (64 KB I cache / 64 KB D cache)
L2 Cache:	128 KB	Cooling Method:	Passive (heat sink)	Flash Memory:	2 MB (for firmware)
Main Memory Type:	DDR SDRAM	Main Memory Quantity:	128 MB	Graphics Controller:	Geode LX800
Graphics Memory:	8 MB shared memory	Sram:	512 KB, Battery-buffered	Ethernet Controller:	Intel 82551ER, NE2000-compatible
Ethernet Transfer Rate:	10/100 MBit/s	Compactflash Type:	Type I	Display Type:	Color TFT, 15 inch (380 mm) diagonal
Last Verified:	11/22/2024 10:40 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

