

B & R Automation - 5LS Expansion Card Series**5LS182.6-1** **Request a Quote**


- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer

Secure Online
CheckoutFree Ground
ShippingOne Year
Warranty

The **5LS182.6-1** is a part of the **5LS Expansion Card Series** by **B & R Automation**.

Specifications

Sram:	1 MB, battery-backed	Fieldbus:	POWERLINK (V1/V2) managing or controlled node	Type:	Type 3
Line Length:	Max. 100 m between 2 stations (segment length)	Transfer Rate:	100 Mbit/s	Physical Layer:	100BASE-TX
Half-duplex:	Yes	Full-duplex:	POWERLINK mode: No / Ethernet mode: Yes	Autonegotiation:	Yes
Auto-mdi/mdix:	Yes	Hub Propagation Delay:	0.96 to 1 us	Operating Temperature:	0 to 55 degrees C
Storage Temperature:	-25 to 70 degrees C	Last Verified:	12/10/2024 6:29 AM		

Contact Us 1620 Old Apex Road, Cary, NC 27513, USA Toll Free: [1-888-551-3082](tel:1-888-551-3082) International: [1-919-443-0207](tel:1-919-443-0207) Fax: [1-919-867-6204](tel:1-919-867-6204) Email: sales@automation-factory.com**Shipping Options****Payment Methods**