

B & R Automation - 5LS Expansion Card Series

5LS187.6



 [Request a Quote](#)

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **5LS187.6** is a part of the **5LS Expansion Card Series** by **B & R Automation**.

Specifications

Interface If1 Type:	CAN bus	Interface If1 Wiring:	4-pin multipoint connector	Interface If1 Maximum Baud Rate:	500 kBit/s
Interface If2 Fieldbus:	ETHERNET Powerlink	Interface If2 Type:	100 Base-T (ANSI/IEEE 802.3)	Interface If2 Wiring:	Shielded RJ45 port
Interface If2 Maximum Baud Rate:	100 MBit/s	Interface If2 Cable Length:	Max. 100 m between two stations (segment length)	Electrical Isolation Pcfx:	Yes
Electrical Isolation If1 If2:	Yes	Sram:	1 MByte, battery backed	Power Input:	4.0 W
Status Display:	Status of the Powerlink station, network activity, link/collision for IF2	Diagnostics Data Transfer If1:	Yes, with software status	Diagnostics Station Status If2:	Yes, with status LED and software status
Last Verified:	12/02/2024 8:51 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

