

B & R Automation - 5PP Power Panel Series

5PP120.1505-37



 [Request a Quote](#)

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **5PP120.1505-37** is a part of the **5PP Power Panel Series** by **B & R Automation**.

Specifications

Boot Loader / Operating System:	BIOS	Processor:	Geode SC2200 266MHz, 32-bit x86	Graphics Controller:	Geode SC2200 with 4 MB shared memory
Display:	15 inch color TFT, XGA, 1024 x 768 pixels	Touch Screen Type:	3M Analog, resistive	Memory:	128 MB DRAM, SO-DIMM 144- pin
Ethernet:	MacPhyter DP83816, 10/100 Mbps	Compactflash Slot:	Type I, 1 slot, Primary IDE device	Usb Interface:	USB 1.1, 2 ports, max. 500 mA per connection
Serial Interface:	RS232, max. 115 kBaud, 9-pin DSUB	Power Supply:	24 VDC ~25%, Max. 20 A for < 1 ms	Power Consumption:	30 W typical, 35 W max.
Battery:	Renata 950 mAh, 4 year lifespan, backup capacitor for 10 minutes	Protection Type:	IP65 (front side), IP20 (back side)	Weight:	Approx. 6.3 kg
Last Verified:	12/20/2024 10:20 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.