

B & R Automation - 8EI Servo Drives

8EI2X2HWD10.0601-1



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty


The **8EI2X2HWD10.0601-1** is a part of the **8EI Servo Drives Series** by **B & R Automation**.


Specifications


Available as 1-axis module:	Yes	Available as 2-axis module:	Yes	Available as 3-axis module:	Yes
Connector Set 1 (1-row):	Yes	Connector Set 2 (2-row):	No	Continuous Current:	2.2 (Aeff)
DC bus capacitance:	470 uF	DC bus continuous power:	2 kW	Fieldbus transfer rate:	100 Mbit/s
Frequency:	50/60 Hz ~4%	Front Cover:	Yes	Input capacitance:	5500 uF
Inrush current:	Max. 45 A	Installed load:	Max. 5 kVA	Internal Braking Resistor:	Yes
Max. cable length:	3 m	Minimum braking resistance (ext.):	25 ?	Module Option:	Standard (no module-specific option)
Module Type:	2-axis module	Mounting:	Wall mounting	Nominal installation elevation:	0 to 500 m above sea level
Overload protection:	Yes	Plug-in Module Type:	No plug-in module included in delivery	Pollution degree per EN 61800-5-1:	2 (non-conductive pollution)
Product Series:	ACOPOS P3 8EI servo drive	Safety Option:	Hardwired STO safety technology with encoder	Voltage:	3x 200-480 VAC


Contact Us


Last Verified: 06/09/2026 9:18 AM

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

