

B & R Automation - 8EI Servo Drives

8EI2X2HWTS0.0600-1



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **8EI2X2HWTS0.0600-1** is a part of the **8EI Servo Drives Series** by **B & R Automation**.

Specifications

Adhesive:	Acrylic	Available as 1-axis module:	Yes	Available as 2-axis module:	Yes
Available as 3-axis module:	Yes	Backing:	Single Sided	Connector Set 1 (1-row):	Yes
Connector Set 2 (2-row):	No	Continuous Current:	2.2 (Aeff)	Customization:	No customized options
Dielectric Strength:	6000 VVmil	Elongation At Break:	20%	Flame Retardant:	Yes
Front Cover:	Yes	Internal Braking Resistor:	Yes	Length:	Standard roll lengths available, custom available
Material:	Polyester	Module Option:	Standard (no module-specific option)	Module Type:	3-axis module
Mounting:	Wall mounting	Plug-in Module Type:	No plug-in module included in delivery	Product Series:	ACOPOS P3 8EI servo drive
Safety Option:	SafeMOTION, with digital encoder	Temperature Range:	-40°C to +120°C (-40°F to +248°F)	Tensile Strength:	60 lbsVin (10.7 kN/m)
Thickness:	0.0600 in (1.52 mm)	UI Recognition:	UL 510		3x 200-480 VAC

Contact Us

Width: 2.00 in (50.8 mm)
Last Verified: 05/18/2026 11:00 AM

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.