

B & R Automation - 8EI Servo Drives

8EI2X2MWTS0.0600-1



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping








One Year
Warranty

The **8EI2X2MWTS0.0600-1** is a part of the **8EI Servo Drives Series** by **B & R Automation**.

Specifications

Available as 1-axis module:	Yes	Available as 2-axis module:	Yes	Available as 3-axis module:	Yes
Conductor Construction:	19 Strands	Conductor Material:	Silver-Plated Copper	Conductor Size:	24 AWG
Connector Set 1 (1-row):	Yes	Connector Set 2 (2-row):	No	Continuous Current:	2.2 (Aeff)
Customization:	No customized options	Front Cover:	Yes	Insulation Material:	Polytetrafluoroethylene (PTFE)
Insulation Thickness:	0.010 inches	Internal Braking Resistor:	Yes	Module Option:	Standard (no module-specific option)
Module Type:	3-axis module No plug-in module included in delivery	Mounting:	Wall mounting	Overall Diameter:	0.0600 inches
Plug-in Module Type:		Product Series:	ACOPOS P3 8EI servo drive	Resistance (max):	26.2 ohms per 1000 feet
Rohs Compliance:	Yes	Safety Option:	SafeMOTION, with digital encoder	Temperature Rating:	200°C
Voltage:	3x 200-230 VAC or 1x 110-230 VAC	Weight:	8.8 lbs per 1000 ft	Wire Color:	White

Contact Us

Last Verified: 06/08/2026 6:47 PM
 1620 Old Apex Road, Cary, NC 27513, USA
 Toll Free: [1-888-551-3082](tel:1-888-551-3082)
 International: [1-919-443-0207](tel:1-919-443-0207)
 Fax: [1-919-867-6204](tel:1-919-867-6204)
 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

