

B & R Automation - 8LS Synchronous Motors

8LSA26.E5060D200-3



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **8LSA26.E5060D200-3** is a part of the **8LS Synchronous Motors Series** by **B & R Automation**.

Specifications

Configuration Summary:	8LSA: Standard, no reinforced bearing	Connection direction:	Angled (swivel)	Connection Hardware:	Connector
Cooling Method:	Naturally cooled	Cooling Principle:	Self-cooling, free circulation	Designation:	8LSA
Encoder Technology:	Optical EnDat	Encoder Type:	Absolute, singleturn, EnDat 2.2	EnDat Version:	2.1
Flange Dimension:	58 (mm)	Holding Brake:	Standard holding brake	Length Code:	6
Motor Type:	Three-phase synchronous	Mounting Availability:	Mounting flange	Mounting Flange Size:	80 mm
Oil Seal:	Not Present	Peak Current:	18.7 A	Peak Torque:	19.1 Nm
Product Revision:	3	Protection Class:	IP65	Rated Current:	5.8 A
Rated Power:	2.0 kW	Rated Speed:	6000 (rpm)	Rated Torque:	6.37 Nm
Rated Voltage:	400 V	Resolution:	13/12 (Single/Multi-turn bits)	Shaft End:	Smooth shaft
Turn Capability:	Multi-turn (4096 revs)	Last Verified:	05/18/2026 7:00 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

