


B & R Automation - 8LS Synchronous Motors

8LSA35.DA030S200-3

 **In-Stock, Ships 3-5 Days**



- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **8LSA35.DA030S200-3** is a part of the **8LS Synchronous Motors Series** by **B & R Automation**.

Specifications

Configuration Summary:	8LSA: Standard, no reinforced bearing	Connection direction:	Single-cable solution (hybrid)	Connection Hardware:	Connector
Cooling Method:	Convection cooled	Cooling Principle:	Self-cooling, free circulation	Designation:	8LSA
Encoder Technology:	Inductive EnDat	Encoder Type:	Single-turn absolute encoder	EnDat Version:	2.2
Flange Dimension:	91.3 (mm)	Frame Size:	35	Holding Brake:	Standard holding brake
Length Code:	5	Motor Type:	Three-phase synchronous	Mounting Availability:	Mounting flange
Oil Seal:	Not Present	Product Revision:	3	Protection Class:	IP65
Rated Power:	600 W	Rated Speed:	3000 (rpm)	Rated Torque:	2.0 Nm
Rated Voltage:	230 V	Resolution:	19/0 (Single/Multi-turn bits)	Shaft End:	Smooth shaft
Shaft Version:	Smooth shaft	Turn Capability:	Single-turn	Last Verified:	05/18/2026 3:59 PM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

