

B & R Automation - 8LS Synchronous Motors

8LSA35.E2060D000-0

 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty



The **8LSA35.E2060D000-0** is a part of the **8LS Synchronous Motors Series** by **B & R Automation**.

Specifications

Configuration Summary:	8LSA: Standard, no reinforced bearing	Connection direction:	Angled (swivel)	Connection Hardware:	Connector
Connection Type:	Plug, axial	Cooling Method:	Self-cooling	Cooling Principle:	Self-cooling, free circulation
Designation:	8LSA	Encoder Type:	Multi-turn absolute, EnDat 2.2	Flange Dimension:	91.3 (mm)
Holding Brake:	Not Present	Length Code:	5	Motor Type:	Three-phase synchronous
Mounting Availability:	Mounting flange	Oil Seal:	Not Present	Protection Class:	IP65
Rated Power:	2.0 kW	Rated Speed:	6000 (rpm)	Rated Torque:	6.37 Nm
Rated Voltage:	230 V	Rotor Inertia:	0.00238 kg·m ²	Shaft Diameter:	19 mm
Shaft End:	Smooth shaft	Last Verified:	05/19/2026 2:24 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.