

B & R Automation - 8LS Synchronous Motors

8LSA36.E3022D100-0



 **In-Stock, Ships 1-2 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **8LSA36.E3022D100-0** is a part of the **8LS Synchronous Motors Series** by **B & R Automation**.

Specifications

Configuration Summary:	8LSA: Standard, no reinforced bearing	Connection direction:	Angled (swivel)	Connection Hardware:	Connector
Connection Type:	Rotatable angular connector EnDat 2.2 absolute multiturn (digital)	Cooling Principle:	Self-cooling, free circulation	Designation:	8LSA
Feedback:		Flange Dimension:	91.3 (mm)	Holding Brake:	Not Present
Length Code:	6	Motor Type:	Three-phase synchronous	Mounting Availability:	Mounting flange
Mounting Flange:	140 mm	Oil Seal:	Not Present	Peak Torque:	24.5 Nm
Protection Class:	IP65	Rated Power:	2.85 kW	Rated Speed:	2200 (rpm)
Rated Torque:	11.2 Nm	Rated Voltage:	400 V	Shaft End:	With key
Size:	36	Last Verified:	05/18/2026 2:27 PM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.