

B & R Automation - 8LS Synchronous Motors

8LSA66.EB022D300-1



 **In-Stock, Ships 1-2 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **8LSA66.EB022D300-1** is a part of the **8LS Synchronous Motors Series** by **B & R Automation**.

Specifications

Configuration Summary:	8LSA: Standard, no reinforced bearing	Connection direction:	Angled (swivel)	Connection Hardware:	Connector
Connector Position Designation:	Rotatable 8LSA	Cooling Method:	Natural convection	Cooling Principle:	Self-cooling, free circulation
Flange Dimension:	190 (mm)	Encoder Technology:	Inductive EnDat	EnDat Version:	2.1
Incremental Encoder:	Standard	Frame Size:	66	Holding Brake:	Standard holding brake
Motor Length:	E	Length Code:	6	Max Torque:	21 Nm
Nominal Torque:	7.0 Nm	Motor Type:	Three-phase synchronous	Mounting Availability:	Mounting flange
Rated Power:	2.2 kW	Oil Seal:	Not Present	Protection Class:	IP65
Resolution:	19/12 (Single/Multi-turn bits)	Rated Speed:	2200 (rpm)	Rated Voltage:	400 V
Turn Capability:	Multi-turn (4096 revs)	Shaft End:	With key	Shaft Version:	Keyed shaft
		Last Verified:	06/09/2026 7:09 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.