

B & R Automation - 8LS Synchronous Motors

8LSA73.DB030S200-3

 **In-Stock, Ships 3-5 Days**



- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping








One Year
Warranty

The **8LSA73.DB030S200-3** is a part of the **8LS Synchronous Motors Series** by **B & R Automation**.

Specifications

CE:	Approved	Configuration Summary:	8LSA: Standard, no reinforced bearing	Connection direction:	Single-cable solution (hybrid)
Connection Hardware:	Connector	Continuous Stall Torque:	3 Nm (typical for this size, check datasheet for exact value)	Cooling Method:	Natural convection
Cooling Principle:	Self-cooling, free circulation	cUR:	Approved	Designation:	8LSA
Durable:	Yes	Enclosure:	IP65 (except shaft end and connector)	Encoder Technology:	Inductive EnDat
EnDat Version:	2.2	Feedback Device:	Single-turn absolute encoder (typical, model-dependent)	Flange Dimension:	190 (mm)
Frame Size:	73	Holding Brake:	Standard holding brake	Length Code:	3
Motor Flange:	Standard 73 mm flange	Motor Type:	Three-phase synchronous	Mounting Availability:	Mounting flange

Contact Us

Not Present
 1620 Old Apex Road, Cary, NC 27513, USA
Oil Seal:
 Toll Free: [1-888-551-3083](tel:1-888-551-3083)
Rated Speed: 3000 (rpm)
 International: [1-919-443-0207](tel:1-919-443-0207)
Supply Voltage: 200 V
 Fax: [1-919-867-6205](tel:1-919-867-6205)
Last Verified: 05/18/2026 9:11 PM
 Email: sales@wakeindustrial.com

Shipping Options






Payment Methods






Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.