

B & R Automation - 8LS Synchronous Motors

8LSA75.D1030D200-3

 **In-Stock, Ships 3-5 Days**



- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **8LSA75.D1030D200-3** is a part of the **8LS Synchronous Motors Series** by **B & R Automation**.

Specifications

Configuration Summary:	8LSA: Standard, no reinforced bearing	Connection direction:	Angled (swivel)	Connection Hardware:	Connector
Cooling Principle:	Self-cooling, free circulation	Designation:	8LSA	Enclosure Type:	IP65
Encoder Technology:	Optical EnDat	Encoder Type:	Multi-Turn Absolute Encoder	EnDat Version:	2.2
Flange Dimension:	190 (mm)	Holding Brake:	Standard holding brake	Length Code:	5
Motor Type:	Three-phase synchronous	Mounting Availability:	Mounting flange	Mounting Flange Size:	100 mm
Oil Seal:	Not Present	Peak Torque:	30 Nm	Product Revision:	3
Rated Current:	8.6 A	Rated Power:	2.6 kW	Rated Speed:	3000 (rpm)
Rated Torque:	10 Nm	Resolution:	25/12 (Single/Multi-turn bits)	Shaft End:	Smooth shaft
Turn Capability:	Multi-turn (4096 revs)	Voltage Constant (ke):	96.2 V/1000rpm	Last Verified:	06/09/2026 1:53 PM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.