

B & R Automation - 8LS Synchronous Motors

8LSA75.E2030D000-0



 Available, Ships in 1-2 weeks

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **8LSA75.E2030D000-0** is a part of the **8LS Synchronous Motors Series** by **B & R Automation**.

Specifications

Base speed:	3000 rpm	Configuration Summary:	8LSA: Standard, no reinforced bearing	Connection direction:	Angled (swivel)
Connection Hardware:	Connector	Continuous torque:	30 Nm	Cooling Principle:	Self-cooling, free circulation
Cross section for B&R motor cable:	4 mm ²	Designation:	8LSA	Flange Dimension:	190 (mm)
Holding Brake:	Not Present	Insulation class of the isolation system per EN 60034-1:	F	IP rating:	IP64
Length Code:	5	Maximum current:	24.5 A	Maximum torque:	40 Nm
Motor Type:	Three-phase synchronous	Mounting Availability:	Mounting flange	Nominal current:	18.4 A
Oil Seal:	Not Present	Operating voltage:	400 V	Rated speed:	3000 (rpm)
Rating class, operating mode per EN 60034-1:	S1 - Continuous operation	Shaft end:	Smooth shaft	Top speed:	4500 rpm
Vibration severity per EN 60034-14:	Vibration severity level A	Last Verified:	05/19/2026 10:32 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

