

B & R Automation - CM16 Motor Cables

8BCH0009.1111A-0



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **8BCH0009.1111A-0** is a part of the **CM16 Motor Cables Series** by **B & R Automation**.

Specifications

Cable Diameter:	13 mm ± 0.4 mm	Cable Length:	9 m	Current-carrying Capacity (wall):	20.2 A
Encoder Type:	Incremental, 2500 ppr	Flange Size:	60 mm	Hybrid Connector Ip Rating (mated):	IP66/67
Hybrid Connector Type:	13-Pin Female SpeedTec	Insulation Resistance (min):	200 M ² ·km	Max Current:	5.4 A
Max Drag Chain Speed:	300 m/min	Min Bend Radius (moving):	100 mm	Outer Jacket Material:	PUR
Power Line Cross Section:	1.5 mm ²	Product Series:	BCH Servo Motor	Protection Class:	IP65
Rated Current:	2.5 A	Rated Power:	0.4 kW	Rated Speed:	3000 rpm
Rated Torque:	1.27 Nm	Rotational Inertia:	0.41 x 10 ⁻⁴ kg·m ²	Shield Coverage (min):	85%
Stall Torque:	1.27 Nm	Supply Line Cross Section:	0.75 mm ²	Test Voltage (wire-wire):	4 kV
Voltage:	230 V	Weight:	2.2 kg	Last Verified:	05/19/2026 6:03 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.