Click to Request a Quote!

sales@automation-factory.com 1-919-443-0207

B & R Automation - X20 Fieldbus Input Output Series

X20DI9372



per EN 61131-2

Type 1



- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer





Secure Online Checkout Free Ground Shipping

One Year Warranty

The X20DI9372 is a part of the X20 Fieldbus Input Output Series by B & R Automation.

Specifications

Nominal Voltage: 24 VDC Input Voltage: 24 VDC -15% / Input Current At 24 VDC -15% / Ydc: Typ. 3.75 mA

Hardware <=100 us, Software Default 1 ms, configurable between 0 and 25

1-wire connections

Input Characteristics: Input Filter: ms in 0.2 ms intervals Connection Type:

Source Typ. 6.4 kohm Switching Threshold <5 VDC

Input Circuit: Input Resistance: Typ. 6.4 konm (low): Operating

Switching Threshold >15 VDC Isolation Voltage Between Channel And 500 V (horizontal

(high): Bus: Mounting):

Operating
-25 to 50
-40 to 85 degrees 01/02/202

Temperature (vertical Mounting):

-25 to 50 degrees C

Storage Temperature:

-40 to 85 degrees

C

Last Verified:

01/02/2025
4:51 AM

Contact Us

💡 1620 Old Apex Road, Cary, NC 27513, USA

J Toll Free: <u>1-888-551-3082</u>

International: <u>1-919-443-0207</u>

<u> </u> Fax: <u>1-919-867-6204</u>

Email: <u>sales@automation-factory.com</u>

Shipping Options









-25 to 60 degrees

Payment Methods









Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.