

Bosch Rexroth Indramat - MS2M Ultra Compact Motors

MS2M03-B0FNN-KMDH1

 **Call For Quote**



- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **MS2M03-B0FNN-KMDH1** is a part of the **MS2M Ultra Compact Motors Series** by **Bosch Rexroth Indramat**.

Specifications

Brake Voltage:	24V DC	Connectors:	M17; Quick lock SPEEDCON	Cooling Mode:	Natural Convection
Encoder:	Optical Encoder (23 Bit)	Encoder Design:	Single/Multiturn	Frame Length:	B
Frame Size:	3	Holding Brake:	Electrically Released Brake	Leadwire Cable:	Double Cable Metal
Maximum Current:	7.23 A	Maximum Torque:	3.82 Nm	Operational Temp Range:	0 to 40 Celsius
Phase Resistance (20 °c):	1.74 Ohm	Product Group:	Ultra Compact Motor	Protection Type:	IP65
Rated Current:	2.40 A	Rated Power:	0.4 kW	Rated Speed:	3000 min-1 Plain Shaft, without shaft sealing ring
Rated Torque:	1.27 Nm	Rotor Inertia:	Low Motor Inertia	Shaft:	
Sound pressure level:	65 dB(A)	Supply Voltage Range:	4.75 to 5.25 V	Torque Constant (20 °c):	0.52 Nm/A
Voltage Constant (1000 Rpm):	18.30 V(rms)	Winding:	3000 min-1	Last Verified:	05/22/2026 3:18 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.