



Bosch Rexroth Indramat - VT-5000 IO Cards

VT 5002 S21



Request a Quote

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **VT 5002 S21** is a part of the **VT-5000 IO Cards Series** by **Bosch Rexroth Indramat**.

Specifications

Aux regulated voltage:	±9 V ±1% (±25 mA)	Card dimensions:	100 x 160 mm (Euro-card, DIN 41494)	Clock frequency:	Self-clocking up to 1.5 kHz
Connector type:	32-pin male, DIN 41612 form D	Current consumption:	<2 A	Front panel height:	3 HE (128.4 mm)
Front panel width (component side):	7 TE	Front panel width (solder side):	1 TE	Fuse rating:	2.5 A time-delay
Load capability:	30 mA per output max	Measuring socket actual value:	0 SPR 6.6 V (Ri=100 ? , SPR 100% to +100%)	Measuring socket command value:	0 SPR 7.6 V (Ri=100 ? , SPR 100% to +100%)
Operating voltage:	24 VDC ±40% (22 SPR 35 V)	Oscillator frequency:	2.5 kHz ±10%	Power consumption:	<50 VA
Solenoid output VT5005/07:	I _{max} 1.8 A ±20%, R ₂₀ =5.4 ?	Solenoid output VT5006/08:	I _{max} 2.2 A ±20%, R ₂₀ =10 ?	Voltage amplitude:	5 V per output
Last Verified:	07/01/2025 6:13 AM				

Contact Us

1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods

