

Bosch Rexroth Indramat - VT-5000 IO Cards

VT-5004-24/R1E



 **In Stock, Ships Today**

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **VT-5004-24/R1E** is a part of the **VT-5000 IO Cards Series** by **Bosch Rexroth Indramat**.

Specifications

Actual Pressure Input (pist):	0SPR10 V, Re >50 k?, RB =100 ?	Auxiliary Voltage for External Use:	±15 V (+2%/? 6%), I _{max} 10 mA	Card dimensions:	100×160 mm (Euro-card, DIN 417494)
Connector Type:	32-pin male, DIN 417612 Form D 1 TE (5.08 mm) solder, 7 TE (35.56 mm) component	Current Consumption:	0.6 A nominal, 1.25 A max	Front panel height:	3 HE (128.4 mm)
Front panel width:	1 V (IW9 swivel), 3.6 V (DM2 valve)	Operating temperature range:	0 to 50 °C	Operating Voltage:	24 V DC, +40%/? 10% (21.6SPR33.6 V)
Oscillator amplitude:	1 V (IW9 swivel), 3.6 V (DM2 valve)	Oscillator frequency:	5.4 kHz	Output Stage Solenoid Current:	I _{max} 2.5 A, R20 =2 ?
Power Command Input (p-sw)max:	0SPR10 V, Re >50 k?	Pressure Command Input (psoll):	0SPR10 V, Re >50 k?	Pressure signal output:	0SPR10 V
Storage temperature range:	?25 to 85 °C	Swivel Angle Command Input (swsoll):	±10 V (opt. 0SPR10 V), Re >50 k?	Swivel angle signal output:	?10 to 10 V (±100%)
Weight:	0.15 kg	Last Verified:	07/12/2025 3:08 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

