

Bosch Rexroth Indramat - VT-5000 IO Cards

VT 5015 S30



 **In Stock, Ships Today**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout





Free Ground
Shipping



One Year
Warranty

The **VT 5015 S30** is a part of the **VT-5000 IO Cards Series** by **Bosch Rexroth Indramat**.

Specifications

Card Dimensions:	Euro-card 100 x 160 mm (DIN 41 494)	Front Panel Dimensions:	Height: 3 HE (128.4 mm); Solder side width: 1 TE (5.08 mm);	Installation And Safety Notes:	Plug/unplug only when disconnected from the power supply; us
Maximum Load Capability:	30 mA	Measuring Sockets Command And Actual Values:	Command   0 to ± 7.6 V (with $R_i = 100 \Omega$); Actual position Options: 1.8 A ($\pm 20\%$) with $R = 5.4 \Omega$ or 2.2 A ($\pm 20\%$) with R	Operating Temperature Range:	0 to 50 °C
Oscillator Frequency:	2.5 kHz $\pm 10\%$	Output Stage Solenoid Current And Resistance:	Up to approx. 1.5 kHz	Ramp Time:	Adjustable from 30 ms to approx. 1 s or 5 s ($\pm 20\%$ each) 32-pin male multipoint connector (DIN 41 612, form D)
Regulated Voltage Supply:	± 9 V $\pm 1\%$; externally loadable with ± 25 mA	Self-clocking Frequency:	0.15 kg	Type Of Connection:	06/30/2025 1:01 PM
Voltage Amplitude Per Output (uss):	5 V	Weight:		Last Verified:	

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

