

Bosch Rexroth Indramat - VT-5000 IO Cards

VT 5062 S11



 [Request a Quote](#)

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **VT 5062 S11** is a part of the **VT-5000 IO Cards Series** by **Bosch Rexroth Indramat**.

Specifications

Actual Output Range (x):	0 to ± 6 V, $R_i=100 \ ?$	Card Dimensions:	Euro-card 100 x 160 mm, DIN 41 494	Clock Frequency:	Up to approx. 1.5 kHz
Command Input Range (w):	± 6 V (-6 V= $+100\%$, +6 V= -100% , $R_i=100 \ ?$	Connection Interface:	32-pin male connector, DIN 41 612, form D	Front Panel Height:	3 HE (128.4 mm)
Front Panel Width (Component Side):	7 TE	Front Panel Width (Solder Side):	1 TE (5.08 mm)	Max Load Current:	30 mA
Operating Temperature Range:	0 to 50 °C	Oscillator Frequency:	2.5 kHz ($\pm 10\%$)	Output Voltage Amplitude:	5 V per output
Ramp Time Adjustment Range:	30 ms to approx. 1 or 5 s ($\pm 20\%$)	Regulated Output Voltage:	± 9 V ($\pm 1\%$), up to ± 25 mA load	Solenoid VT 5005/VT 5007 Current:	1.8 A ($\pm 20\%$)
Solenoid VT 5005/VT 5007 Resistance:	5.4 ?	Solenoid VT 5006/VT 5008 Current:	2.2 A ($\pm 20\%$)	Solenoid VT 5006/VT 5008 Resistance:	10 ?
Weight:	0.15 kg	Last Verified:	07/12/2025 2:51 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

