



Copley Controls - Accelnet CanOPEN Modules

ADP-060-40



Request a Quote

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **ADP-060-40** is a part of the **Accelnet CanOPEN Modules Series** by **Copley Controls**.

Specifications

Analog Command Input:	±10 Vdc differential, 5 k Ω impedance	CAN Port Protocol:	CANopen Device Profile CiA 402	CANopen Communication Profiles:	Position, Velocity, Torque, PVT, Homing
Cooling Requirement:	Heat sink or forced air cooling for continuous operation	Digital Inputs:	12	Digital Outputs:	3
Dimensions:	167 × 98.8 × 29.7 mm (6.58×3.89×1.17 in)	Encoder Port Frequency:	5M lines/s, 20M counts/s (quadrature)	Operating Ambient Temperature:	0 to +45°C
Position Reference Input:	Step/Direction, CW/CCW up to 2 MHz	PWM Frequency Range:	1 kHz to 100 kHz	RS-232 Baud Rate:	9,600 to 115,200 Baud
Shock Compliance:	10 g, 10 ms half-sine pulse, IEC 60068-2-27	Vibration Compliance:	2 g, 10-500 Hz sine, IEC 60068-2-6	Weight:	0.94 lb (0.43 kg)
Last Verified:	05/23/2025 11:55 AM				

Contact Us

1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.