



Copley Controls - Accelnet CanOPEN Modules

BPL-090-14



Request a Quote

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **BPL-090-14** is a part of the **Accelnet CanOPEN Modules Series** by Copley Controls.

Specifications

Auxiliary HV Supply Voltage:	+14 to +90 Vdc (optional)	Certifications:	UL 61800-5-1, TÜV IEC 61508, ISO 13849-1	Communication Interface:	RS-232
Continuous Current (per phase):	7 A DC (5 A RMS)	Dimensions with heatsink:	5.08 x 3.41 x 3.39 in	Dimensions without heatsink:	5.08 x 3.41 x 1.99 in
Feedback Support:	Incremental encoders, Hall sensors, resolver	Operating Temperature:	0 to +45 °C	Peak Current (per phase):	14 A DC (9.9 A RMS) ±5%
Protection:	Short circuits, over-temperature, feedback loss	Resolution:	12-bit	Safe Torque Off (STO):	SIL 3, Category 3, PL d
Signal Protocol:	CANopen	Storage Temperature:	-40 to +85 °C	Weight with heatsink:	1.70 lb (0.77 kg)
Weight without heatsink:	0.75 lb (0.34 kg)	Last Verified:	05/24/2025 5:37 AM		

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.