

Copley Controls - Copley Controls Accessories

XSL-FA-01



In Stock, Ships in 3-5 Days

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **XSL-FA-01** is a part of the **Copley Controls Accessories Series** by **Copley Controls**.

Specifications

Agency Approvals:	UL508C, EN60204	Common Mode Inductance:	220 μ H (nominal)	Cooling Requirements:	No fan with XSL-230-18/230-36; fan for XSL-40 >12 Adc
Differential Mode Inductance (per phase):	82 μ H (nominal)	Differential Mode Inductance (phase to phase):	162 μ H (nominal)	Input Connector Type:	Euro-style 5-pos, 5.0 mm pluggable terminal block
Maximum Current:	20 Adc	Maximum Voltage:	373 Vdc	Output Connector Type:	Euro-style 4-pos, 5.0 mm pluggable terminal block
Peak Current (1 s):	40 Adc	Recommended Wire:	12 AWG, 600 V	Resistance per leg:	27 m Ω (nominal)
Resistance phase to phase:	54 m Ω (nominal)	Rise/Fall Time:	500 ms (typical)	Last Verified:	05/03/2025 10:50 PM

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.