



Copley Controls - Copley Controls Accessories

XTL-HL



Request a Quote

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **XTL-HL** is a part of the **Copley Controls Accessories Series** by **Copley Controls**.

Specifications

Accessory class:	HL	Accessory type:	Heatsink	Bus Voltage Compensation:	Changes in bus or mains voltage do not affect bandwidth
Dimensions (with XTL device):	192 x 142 x 65 mm (7.6 x 5.6 x 2.6 in)	Field installation options:	Low-profile, thermal, hardware	Max mains current (1Ø, with XTL device):	20.0 A rms
Motor outputs:	Phase U, V, W PWM outputs	Overvoltage protection:	Trips at >400 Vdc; PWM off until HV <400 Vdc	Supported motor config:	3-phase ungrounded Wye or delta brushless motors
Weight (accessory only):	0.57 kg (1.26 lb)	Weight (with XTL device):	1.98 kg (4.26 lb)	XTL absolute encoder:	BiSS C unidirectional
XTL CANopen protocol:	Device Profile DSP-402	Last Verified:	05/23/2025 5:15 PM		

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods

