

Copley Controls - DC Servo Amplifiers

5131



<table-of-contents> Request a Quote

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer

Ċ
Secure Online

Checkout

Free Ground

Shipping



One Year Warranty

The **5131** is a part of the **DC Servo Amplifiers Series** by **Copley Controls**.

-15 VDC output:	5 mA	+15 VDC output:	5 mA	+5 VDC output:	250 mA
Continuous output current:	15 A @ 85 V	Dimensions (W×L×H):	3.82 × 6.57 × 1.37 in	Input voltage range:	2450 VDC
Load inductance range:	200 µH ∰40 mH	Minimum power consumption:	2.7 W	Operating temperature range:	0₽₽¶70 °C (baseplate)
Output short-circuit protection:	Yes	Over/under voltage protection:	Yes	Overtemperature latching:	Yes
Peak output current:	30 A @ 83 V	PWM switching frequency:	25 kHz	Reference input:	Differential, 94 k?, 20 V max
Short-circuit latching:	Yes	Small signal bandwidth (-3 dB):	3 kHz	Weight (without heatsink):	1.1 lb

Contact Us

Last Verified:

Specifications

♀ 1620 Old Apex Road, Cary, NC 27513, USA

05/23/2025

5:49 AM

- 🤳 Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- 둼 Fax: <u>1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.