

sales@automation-factory.com 1-919-443-0207

#### **Copley Controls - XENUS Digital Loop Modules**

# XE2-230-20



IEC 61500 1 IEC

## In Stock, Ships in 3-5 Days

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer



Free Ground Shipping

One Year Warranty

The XE2-230-20 is a part of the XENUS Digital Loop Modules Series by Copley Controls.

## Specifications

IEC 61508-1, IEC 61508-2, IEC 61800-3, SEMI F47-0706	Continuous Current:	10 Adc	Control Power:	+24 Vdc, ±10%
Current, velocity, position	Dimensions:	9.24 x 5.42 x 3.59 [234.7 x 137.6 x 91.1]	EtherCAT Ports Protocol:	CAN application layer over EtherCAT (CoE)
20 Apeak @ 120 Vac, 40 Apeak @ 240 Vac	Mains Current:	18 Arms, 1 Ø; 14 Arms, 3 Ø	Mains Voltage, Frequency:	100~240 Vac, 50/60 Hz
20 Adc	Peak Time:	1 s	Safety Integrity Level	SIL 3, Category 3, PL d
Current loop: 16 kHz, Velocity & position loops: 4 kHz 05/03/2025 7:05 PM	Weight:	4.19 lb [1.90 kg]	Wire Types:	Twisted, shielded conductors
	61508-2, IEC 61800-3, SEMI F47-0706 Current, velocity, position 20 Apeak @ 120 Vac, 40 Apeak @ 240 Vac 20 Adc Current loop: 16 kHz, Velocity & position loops: 4 kHz 05/03/2025	61508-2, IEC 61800-3, SEMI F47-0706Continuous Current:Current, velocity, positionDimensions:20 Apeak @ 120 Vac, 40 Apeak @ 240 VacMains Current:20 AdcPeak Time:Current loop: 16 kHz, Velocity & position loops: 4 kHzWeight:	61508-2, IEC 10 Adc   61508-2, IEC 10 Adc   61800-3, SEMI Continuous Current:   F47-0706 0.24 × 5.42 ×   Current, velocity, position 9.24 × 5.42 ×   20 Apeak @ 120 137.6 × 91.1]   Vac, 40 Apeak @ 18 Arms, 1 Ø; 14   Arms, 3 Ø Arms, 3 Ø   20 Adc Peak Time: 1 s   Current loop: 16 4.19 lb [1.90 kg]   kHz 05/03/2025 Weight:	61508-2, IEC 61800-3, SEMI F47-070610 AdcCurrent, velocity, position09.24 x 5.42 x 3.59 [234.7 x)Control Power:20 Apeak @ 120 Vac, 40 Apeak @ 240 VacDimensions:137.6 x 91.1]EtherCAT Ports Protocol:20 AdcMains Current:18 Arms, 1 Ø; 14 Arms, 3 ØMains Voltage, Frequency:20 AdcPeak Time:1 sSafety Integrity Level:Current loop: 16 kHz, Velocity & position loops: 4 kHzWeight:4.19 lb [1.90 kg]Wire Types:

#### **Contact Us**

- 9 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

### **Shipping Options**



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.