

Copley Controls - XENUS Digital Loop Modules

XPC-230-09



 **In Stock, Shipping Varies**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **XPC-230-09** is a part of the **XENUS Digital Loop Modules Series** by **Copley Controls**.

Specifications

Continuous Current: 3 A (2.12 A rms)

Control Modes:

Position,
Velocity, Torque,
Interpolated
Position, Homing
Opto-isolated
SSR, 300 mA
max, 24 V
tolerant

**Current Loop
Sampling Rate:**

16 kHz (62.5 μ s)

Digital Loop Control: 100% digital

Digital Outputs:

Dimensions:

191.4 x 115.6 x 54.1 mm
(7.54"x4.55"x2.13")

Feedback: Incremental
quad A/B,
sin/cos analog,
SSI encoder

Input Power:

100-240 V AC

Interfaces:

CANopen, RS-232,
ASCII, discrete I/O,
Stepper commands

Peak Current: 9 A (6.4 A rms)

Regeneration Power:

20 W
continuous,
2500 W peak
05/23/2025
3:38 PM

Safety Integrity Level:

SIL 3 (Cat 3, PL d)

Weight: 1 kg (2.2 lbs)

Last Verified:

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.