

Copley Controls - XENUS Digital Loop Modules

XSL-230-36



 **In Stock, Ships 2-3 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **XSL-230-36** is a part of the **XENUS Digital Loop Modules Series** by Copley Controls.

Specifications

Ambient operating temperature:	0 to +45 °C	Command interfaces:	CANopen; ASCII; discrete I/O; stepper; ±10V; PWM	Communications:	CANopen; RS232
Continuous AC current:	8.5 Arms (sinusoidal)	Continuous DC current:	12 Adc	Control modes:	PTP,PVT,camming,gearing,position,velocity,torque,indexing
Cooling:	Heatsink and/or forced air cooling	Current loop sampling rate:	15 kHz	Digital I/O:	12 inputs; 4 outputs
Dimensions (inches):	7.5 x 5.5 x 2.5 in	Dimensions (mm):	191 x 140 x 64 mm	Feedback types:	Quadrature A/B; secondary; sin/cos analog; resolver; Hall
Peak AC current:	25.5 Arms (sinusoidal)	Peak DC current:	36 Adc	Power supply:	100-240 VAC ±10%, 1Ø/3Ø, 47-63 Hz
Storage temperature:	-40 to +85 °C	Velocity & position sampling rate:	3 kHz	Weight (without heatsink):	3.0 lb (1.36 kg)

Contact Us
 Verified: 05/03/2025 6:12 PM
 1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.