

Danaher - Dynapar Encoders

2201001003



Specifications

±40°/PPR (±14 ±10.8°/PPR (±3.9 NEMA4/IP66, **Accuracy (Opposite** arc?sec at 10,000 Accuracy (Same arc?sec at 10,000 dustproof Channel): washdown PPR) Channel): PPR) **Enclosure Rating:** Incremental optical, two? ?300 kHz ?200 kHz **Frequency Response Frequency Response** channel quad AB **Encoder Type:** (Line Driver): (Push?Pull): + index Z Input Power (Line 5 VDC ±10%, 40 **Input Power (Push?** 10 SP#30 VDC, 60 **Maximum Shaft** 10,000 RPM max Driver): mA max Pull): mA max Speed: A leads B for CCW rotation 0 to +70 °C 90° ±25° electrical Operating (viewed at shaft **Temperature:** Phase Sense: **Quadrature Phasing:** end) 8192 to 10,000 35 lbs radial, 24 3/8 in **Resolution:** PPR Shaft Loading: lbs axial Shaft Size: 07/16/2025 ₽#25 to +90 °C **Storage Temperature:** Last Verified:

4:02 AM

Contact Us

- 1620 Old Apex Road, Cary, NC 27513, USA
- Toll Free: 1-888-551-3082
- International: 1-919-443-0207
- Fax: <u>1-919-867-6204</u>
- Email: sales@automation-factory.com

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.

Request a Quote

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer

. Secure Online Checkout

Free Ground Shipping

One Year Warranty

The **2201001003** is a part of the **Dynapar Encoders** Series by Danaher.