

Danaher - Dynapar Encoders

AI2512142192F



Specifications

Communication Protocol:	Modbus	Current Rating:	5 A	Dimensions:	50 mm x 30 mm x 15 mm
Frequency Range:	50 Hz - 60 Hz	Ingress Protection:	IP67	Interface:	4-20 mA
Material:	Aluminum Alloy	Mounting Type:	Panel Mount	Operating Temperature:	-20degrees C to 70degrees C
Operating Voltage:	24 V DC	Output Options:	Incremental and absolute output options	Power Consumption:	120 W
	Up to 10,000 pulses per	Shock and Vibration	Shock up to 50G and vibrations up		200 grams
Resolution:	revolution 07/16/2025	Resistance:	to 10G	Weight:	
Last Verified:	1:45 PM				

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- 🤳 Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.

Request a Quote

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Checkout

لمان Free Ground

Shipping

One Year Warranty

The Al2512142192F is a part of the Dynapar Encoders Series by Danaher.