

Danfoss - VLT 2800 Low Voltage Drives

195N0006



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **195N0006** is a part of the **VLT 2800 Low Voltage Drives Series** by **Danfoss**.

Specifications

Analog I/O Resolution:	10-bit	Application Option:	No application option	Coating:	Without coating
Control Type:	SB (integrated brake chopper) Built In Display (SLCP)	Dedicated Application:	Process	Dimensions (h X W X D):	200 x 90 x 152 mm
Display:		Enclosure Type:	Bookstyle	Fieldbus Option:	DeviceNet
Frequency Range:	0 to 1000 Hz	Hardware Configuration:	Standard with brake	Input Voltage:	1 x 220-240 V / 3 x 200-240 V 180% for 0.5 seconds
Mains Voltage U(in):	200-240V AC	Motor Power:	0.37 kW	Peak Starting Torque:	seconds
Product Group:	VLT	Profibus:	No	Protection Rating:	IP20
Ramp Time Range:	0.02-3600 seconds	RFI Filter:	Without filter (No EMC)	Switching at Input:	2 times/min allowed
Switching at Output:	Indefinite	VLT Series:	2800	Weight:	3.8 kg
Last Verified:	06/09/2026 8:08 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

