

Danfoss - VLT 2800 Low Voltage Drives

195N1017



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping




One Year
Warranty

The **195N1017** is a part of the **VLT 2800 Low Voltage Drives Series** by **Danfoss**.

Specifications

Ambient Temperature (max):	45 °C	Applicable Series:	VLT 2803-2875 RFI 1B filter	Application Option:	No application option
Coating:	Without coating	Compliance Standard:	EN 55011-1B	Dedicated Application:	Process
Dimensions (h X W X D):	200 x 60 x 87 mm	Display:	Built In Display (SLCP)	Enclosure Rating:	IP20
Enclosure Type:	Bookstyle	Hardware Configuration:	Standard	Horse Power:	1.0 HP
Mains Voltage U(in):	380-480V +/- 10% 50/60Hz	Max Output Frequency (with Lc):	120 Hz	Max. Cable Length (screened 200-240 V):	100 m
Max. Cable Length (screened 380-480 V):	25 m	Max. Rated Current:	16 A	Max. Voltage:	480 V AC
Max. Voltage To Earth:	300 V AC	Min. Distance Above/below:	100 mm	Min. Distance Between Filter And Vlt:	Side-by-Side
Mounting:	Vertical mounting only	Phase:	3 phase	Power Rating:	0.75kW
Product Group:	VLT	Protection Rating:	IP20	RFI Filter:	Without filter (No EMC)
Thermistor (ptc):	Integral	VLT Series:	2800	Weight:	0.9 kg

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

