

Danfoss - VLT 2800 Low Voltage Drives

195N1038



 **In-Stock, Ships 1-2 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **195N1038** is a part of the **VLT 2800 Low Voltage Drives Series** by **Danfoss**.

Specifications

Application Option:	No application option	Coating:	Without coating	Dedicated Application:	Process
Dimensions (h X W X D):	200 x 90 x 152 mm	Display:	Built In Display (SLCP)	Enclosure Type:	Bookstyle
Fieldbus Option:	Without fieldbus option	Functional Type:	Motor Coil Module	Hardware Configuration:	Standard with brake
Horse Power:	2.0 HP	Mains Voltage U(in):	380-480V +/- 10% 50/60Hz	Max Cable Length (screened):	100 m
Max Cable Length (unscreened):	200 m	Max Rated Current:	16 A	Max Voltage To Earth:	300 V AC
Min Distance Above/below:	100 mm	Minimum Distance (side By Side):	Direct, no gap	Mounting Orientation:	Vertical mounting only
Phase:	3 phase	Power Rating:	1.5kW	Product Group:	VLT
Protection Rating:	IP20	RFI Filter:	Without filter (No EMC)	System Compatibility:	Danfoss VLT 2800 Series
Usage With Switching Frequency:	4500 Hz	VLT Series:	2800	Weight:	3.8 kg
Last Verified:	05/26/2026 1:12 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

