

Danfoss - VLT 2800 Low Voltage Drives

195N1041



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **195N1041** is a part of the **VLT 2800 Low Voltage Drives Series** by **Danfoss**.

Specifications

Application Option:	No application option	Coating:	Without coating	Dedicated Application:	Process
Dimensions H X W X D (mm):	200 x 90 x 152	Display:	Built In Display (SLCP)	Enclosure Type:	Bookstyle
Hardware Configuration:	Standard	Horse Power:	2.0 HP	Mains Voltage U(in):	380-480V +/- 10% 50/60Hz
Max Cable Length (200-240 V):	100 m	Max Cable Length (380-480 V):	25 m	Max Rated Current:	16 A
Max Voltage:	480 V AC	Max Voltage To Earth:	300 V AC	Min Distance Above/below Filter:	100 mm
Min Distance Side-by-side:	None required	Mounting:	Vertical mounting only	Phase:	3 phase
Power Rating:	1.5kW	Product Group:	VLT	Protection Rating:	IP20
RFI Filter:	Without filter (No EMC)	Switching Frequency:	4500 Hz	VLT Series:	2800
Weight:	3.8 kg	Last Verified:	06/09/2026 9:15 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

