

Danfoss - VLT 2800 Low Voltage Drives

195N1100



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **195N1100** is a part of the **VLT 2800 Low Voltage Drives Series** by **Danfoss**.

Specifications

Application Option:	No application option	Cable Length Screened:	100 m	Cable Length Unscreened:	200 m
Coating:	Without coating	Compliant Standard:	EN 55011-1A	Dedicated Application:	Process
Dimensions H X W X D:	200 x 90 x 152 mm	Display:	Built In Display (SLCP) Without fieldbus option	Enclosure Rating:	IP 20
Enclosure Type:	Bookstyle	Fieldbus Option:		Frequency Range:	Up to 4500 Hz
Hardware Configuration:	Standard with brake	Horse Power:	10 HP	Mains Voltage U(in):	380-480V +/- 10%
Max Rated Current:	16 A	Max Voltage:	480 V AC	Max Voltage To Earth:	300 V AC
Min Distance Above/below:	100 mm	Min Distance Side-by-side:	0 mm	Mounting Orientation:	Vertical only
Phase:	3 phase	Power Rating:	7.5kW	Product Group:	VLT
Protection Rating:	IP20	RFI Filter:	EN 55011 Class A1	Suitable Inverter Models:	VLT 2803-2875
VLT Series:	2800	Weight:	3.8 kg	Last Verified:	06/09/2026 6:04 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

