

Danfoss - VLT 2800 Low Voltage Drives

195N1104



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **195N1104** is a part of the **VLT 2800 Low Voltage Drives Series** by **Danfoss**.

Specifications

Application Option:	No application option	Coating:	Without coating	Dedicated Application:	Process
Dimensions (hwxwd):	200 x 90 x 152 mm	Display:	Built In Display (SLCP)	Enclosure Rating:	IP20
Enclosure Type:	Bookstyle	Hardware Configuration:	Standard with brake	Horse Power:	10 HP
Mains Voltage U(in):	380-480V +/- 10% 50/60Hz	Max Cable Length (screened):	100 m	Max Cable Length (unscreened):	200 m
Max Rated Current:	16 A	Max Voltage:	480 V AC	Max Voltage To Earth:	300 V AC
Min Distance Above/below Coil:	100 mm	Mounting:	Vertical only	Phase:	3 phase
Power Rating:	7.5kW	Product Group:	VLT	Protection Rating:	IP20
RFI Filter:	EN 55011 Class A1	Side-by-side Mounting:	Permitted	Switching Frequency Parameter:	411 = 4500 Hz
VLT Series:	2800	Weight:	3.8 kg	Last Verified:	05/26/2026 1:00 PM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@wakeindustrial.com

Shipping Options



Payment Methods

