

Danfoss - VLT EZ FC 321 Automation Drives

FC-321P1K5T5E20H2BGXXXXSXXXAXBXCXXXDX



4.1 A

Specifications

Continuous Current:Enclosure:IP20Gross Weight:5.2 kgOperating
Temperature Range:-10°C to 50°CPower Rating:1.5 kW / 2.0 HP
05/11/2025Last Verified:7:24 AM

Dimensions: Frame Size:

Output Voltage: Rated Power:

Input Voltage:



1-919-443-0207

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer



60



Secure Online Checkout Free Ground Shipping One Year Warranty

The **FC-**

321P1K5T5E20H2BGXXXXSXXXAXBXCXXXDX is a part of the VLT EZ FC 321 Automation Drives Series by Danfoss.

| 268 mm (Height) x 90 mm (Width) x 205 mm | | > 85% |
|--|-----------------------|-------------------------------|
| (Depth) | Efficiency: | |
| A2 | Frequency: | 50/60 Hz |
| 380-500 VAC | Intermittent Current: | 6.56 A |
| 12 VDC | Panel: | Graphical Loc. Cont. Panel |
| 1200 W | RFI Filter: | Class A2 (C3) |

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- 🤳 Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.