

Danfoss - VLT FC 202 AQUA Drives

FC-202P18KT4E66H2XGC3SXSXXXXAXBXCXXXXDX

 **In Stock, Ships 2-3 Days**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty



The **FC-202P18KT4E66H2XGC3SXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 202 AQUA Drives Series** by **Danfoss**.

Specifications

Continuous Input Current:	29 A at 400 V	Continuous Output Current:	27 A (380 ^{SFR} 440 V), 25 A (441 ^{SFR} 500 V)	Dimensions (h X W X D):	300 mm x 200 mm x 150 mm
Frequency:	50/60 Hz	Input Current:	30 A	Intermittent Current:	32 A (380 ^{SFR} 440 V), 29 A (441 ^{SFR} 500 V)
Isolation:	Category III	Mounting:	Panel mount	Operating Temperature Range:	-10°C to +60°C
Phase:	3-Phase	Power Loss:	291 W	Rated Power:	15 kW
Rated Voltage:	400 V AC	Weight:	15.5 kg (34.2 lb)	Last Verified:	05/09/2025 10:26 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

