



Danfoss - VLT FC 280 Midi Drives

FC-280P4K0T4H2BNCXXXSXXXXAN



 **In Stock, Shipping Varies**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-280P4K0T4H2BNCXXXSXXXXAN** is a part of the **VLT FC 280 Midi Drives Series** by **Danfoss**.

Specifications

Analog inputs:	6 or 79 channels	Control structure:	Open loop	Depth range:	168 ^{SFR} 245 mm
Derating method:	Automatic	Digital inputs:	19 or 79 channels	Efficiency:	78 ^{SFR} 83%
Enclosure sizes:	K1, K2, K3, K4, K5	Height range:	210 ^{SFR} 410 mm	Ingress protection:	IP20
Input power phases:	Single-phase, three-phase	Motor output voltage:	200 ^{SFR} 240 V, 380 ^{SFR} 480 V	Mounting hole pattern:	198×60 to 390×120 mm
Noise level:	< 84 dB	Operating temperature range:	-10°C to 50°C	Power range:	0.37 ^{SFR} 22 kW (3-phase 380 ^{SFR} 480 V)
Pulse inputs:	80 channels	Safety rating:	SIL2	Weight range:	2.5 ^{SFR} 11.5 kg
Width range:	75 ^{SFR} 150 mm	Last Verified:	05/02/2025 8:28 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.