

Danfoss - VLT FC 301 Automation Drives

FC-301P15KT4E20H1XGXXXXSXXX



 **Request a Quote**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-301P15KT4E20H1XGXXXXSXXX** is a part of the **VLT FC 301 Automation Drives Series** by **Danfoss**.

Specifications

Continuous Output Current (380-440 V):	32 A	Diameter:	33 mm	Efficiency:	0.97 at nominal load
Intermittent Overload Current (380-440 V):	51.2 A	L1 Dimension:	32 mm	L2 Dimension:	43 mm
Maximum Ambient Temperature:	50°C (derating above 45°C)	Maximum Pressure:	630 bar for tapered ports Caution specifications	Motor Compatibility:	Shielded: 50 m, Unshielded: 75 m
Nominal Pressure:	400 bar	Steel Version:		Storage Temperature:	-25°C to +70°C
Thread Type:	M 22 x 1.5 taper	Weight:	17.9 kg/ 100 pc.	Last Verified:	05/09/2025 8:56 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.