

Danfoss - VLT FC 301 Automation Drives

FC-301P1K1T4E2H2XGXXXXSXXXXAXBXCXXXXDX

 [Request a Quote](#)



- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-301P1K1T4E2H2XGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 301 Automation Drives Series** by **Danfoss**.

Specifications

Can Interfaces:	2	Digital Inputs:	4 programmable inputs, 0-24 V DC	Enclosure Type:	IP21 (NEMA Type 1)
Input Voltage Range:	100-240 VAC	Interfaces:	2 CAN interfaces	Intermittent Current:	3.4 A (60-second overload)
Isolation:	Electrically isolated Screw-in module, order TB712 terminal block separately	Motor Cable Length (Shielded):	50 m (164 ft)	Motor Cable Length (Unshielded):	75 m (246 ft)
Mounting:		Network Capability:	Yes	Power Consumption:	14.5 W
Power Supply:	100-240 VAC	Pulse Frequency:	0-110 kHz	Type:	Controller Module
Last Verified:	05/09/2025 2:36 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.